

Easymount Sign is designed to perform and built to last.



▲ EM-S1600H

### KEY FEATURES

- Up to 5m/16ft a minute
- Heat Assist & Cold options available
- 25mm/1" mounting thickness
- Large diameter rollers
- Variable speed control
- Built-in media take-up unit
- Self gripping mandrels
- Magic eye safety feature
- Heated roller
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Handy reverse mechanism
- Foot pedal

### GREAT FOR USE IN

- Sign makers
- Print finishers

### IDEAL WHEN LAMINATING

- Single banners
- Reel-to-reel laminates
- Posters, graphics and signs
- Mounting prints to boards
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

Scan with your smartphone to watch the video



### Design & Performance

This Easymount<sup>®</sup> Sign laminator is designed to perform and built to last, with its solid heavy duty construction.

An easy-to-use laminating system with self gripping mandrels and a flip down feed tray.

The Easymount<sup>®</sup> Sign includes an integral media take-up unit, making the system ideal for single banners or reel-to-reel laminating up to 50m.

The Easymount<sup>®</sup> Sign is available as a hot or cold option, in both 1.4m and 1.6m widths.

\*Heated roller available on EM-S1400H & EM-S1600H models.

### INCLUDES

- BUILT-IN MEDIA TAKE-UP UNIT
- SELF GRIPPING MANDRELS
- SINGLE LIFT MECHANISM

| Specifications                 | Heat Assist                      |                                  | Cold                         |                              |
|--------------------------------|----------------------------------|----------------------------------|------------------------------|------------------------------|
|                                | EM-S1400H                        | EM-S1600H                        | EM-S1400C                    | EM-S1600C                    |
| Laminating Speed (m/ft/min)    | up to 5m/16ft                    | up to 5m/16ft                    | up to 5m/16ft                | up to 5m/16ft                |
| Max. Width (mm/inches)         | 1420mm/56"                       | 1620mm/64"                       | 1420mm/56"                   | 1620mm/64"                   |
| Mounting Thickness (mm/inches) | 25mm/1"                          | 25mm/1"                          | 25mm/1"                      | 25mm/1"                      |
| Roller Diameter (mm/inches)    | 130mm/5"                         | 130mm/5"                         | 130mm/5"                     | 130mm/5"                     |
| Laminating Temperature (°C/°F) | 45°C/113°F - can be switched off | 45°C/113°F - can be switched off | -                            | -                            |
| Pressure Adjustment            | Manual                           | Manual                           | Manual                       | Manual                       |
| Film Core (mm/inches)          | 77mm/3"                          | 77mm/3"                          | 77mm/3"                      | 77mm/3"                      |
| Power Supply AC (V-Hz)         | 220/240-50-60                    | 220/240-50-60                    | 220/240-50-60                | 220/240-50-60                |
| Power Consumption (W)          | 1000                             | 1200                             | 38                           | 38                           |
| Overall Dimensions (mm/inches) | 1846x550x1365mm<br>73x22x54"     | 2046x550x1365mm<br>81x22x54"     | 1846x550x1365mm<br>73x22x54" | 2046x550x1365mm<br>81x22x54" |
| Gross Machine Weight (Kg/lbs)  | 136Kg/300lbs                     | 156Kg/344lbs                     | 136Kg/300lbs                 | 156Kg/344lbs                 |
| Gross Stand Weight (Kg/lbs)    | 25Kg/55lbs                       | 30Kg/66lbs                       | 25Kg/55lbs                   | 30Kg/66lbs                   |
| Warranty*                      | 1 year                           | 1 year                           | 1 year                       | 1 year                       |

\*For full terms & conditions on parts and labour warranty, visit [vivid-online.com/support/warranty\\_information](http://vivid-online.com/support/warranty_information)

### Vivid Laminating Technologies Ltd

Matrix House, Norman Court, Ivanhoe Business Park,  
Ashby de la Zouch, Leicestershire LE65 2UZ England

[vivid-online.com](http://vivid-online.com)

+44 (0)845 1 30 40 50 [sales@vivid-online.com](mailto:sales@vivid-online.com)

Vivid care about the environment and is an ISO 14001 registered company.

/vividlaminating

@vividlaminating

/vividlaminating